

# MigMatic® S400iP/MP S400iP

## Synergic Pulsed MIG System

**MIG/MAG (CV)**  
Welding System 

### Quick Specs



#### Industrial Applications

General industrial fabrication  
Construction  
Railcars  
Mobile machinery  
Shipbuilding

#### Processes

MIG/MAG (GMAW)  
Pulsed MIG (GMAW-P)  
Double Pulsed MIG  
Flux-cored (FCAW)  
Lift Tig (MP Model)  
MMA (MP Model)

#### Input Power

400 V, 3 phases (50/60 Hz)

#### Welding Output

400 A, 34 V at 80% duty cycle  
400 A, 34 V at 100% duty cycle (MP model)

#### Max. Output Amperage

440 A

#### Output Range

15 A – 400 A

#### Net Weight

Power source: 53 kg  
Wire feeder: 18 kg  
Cooler: 23 kg

### Performance / Durability / Productivity

**NEW!**

Miller MigMatic® S400iP and MP S400iP synergic Pulsed MIG/MAG System offers full flexibility. All modules are bespoke to the system and designed for trouble free, high productivity welding. Never before has it been so easy and straight forward to achieve excellent welding performance. Enjoy full control at all times.

#### Trigger program switch

Re-call up to 4 preset programs from the torch trigger (any standard MIG torch) for increased productivity on complex objects.

#### Multiprocess

A new multiprocess version is now available enabling lift TIG and MMA.

#### MigMatic Feed 2.0

A new generation of feeder has been developed to step up the user experience and quality of the MigMatic family.

#### Miller robustness

Tested and approved for heavy duty welding under the toughest conditions. Miller goes to extreme measures to ensure trouble free welding in any environment.

#### Energy efficient

The Fan-On-Demand™ power source cooling system operates only when needed, reducing the amount of contaminants pulled through the machine. The MigMatic® Cool is controlled and monitored by the power source and runs only when needed, reducing noise and the overall energy use.

#### Full synergic Pulse with presets

Synergic lines for all common wire/gas combinations with presets of start/stop parameters for optimal welds.

#### Wind Tunnel Technology™

Internal air flow that protects electrical components and PC boards from dirt, dust and debris, greatly improving reliability.

#### Ease of use and versatility

New display with a larger size and higher clarity.



Easy to use



#### Versatility

- Compatible with Push/Pull torches (optional accessory kit).
- Optional connection for automation.
- Upgradable from air cooled to water cooled without any modification to the machine or trolley.
- Suspension hook and wheel kit for the wire feeder for increased reach.
- Cable management system keeping the interconnection cable off the floor.
- Compatible with On-torch control of wire feed speed and voltage.



Warranted for three years, parts and labour.



#### International Headquarters Miller Electric Mfg. LLC

An ITW Welding Company  
1635 W. Spencer Street  
Appleton, WI 54914 USA

MillerWelds.com/europe

#### Miller Europe

Orbitalum Tools GmbH  
Josef Schuettler Str. 17  
78224 Singen, Germany

Tel.: +49 7731 792 400  
sales.MILLER@ITWwelding.com

#### UK sales office

Tel.: +44 1695 58 59 11

## New MigMatic Feed design

### Hardware upgrade:

- More compact
- Screen incline
- Updateable through USB port
- Easy to carry
- Full protection for water hoses
- Push encoder
- Gun holder



### Upgraded UI:

- Better clarity
- Larger size
- Improved accessibility to settings
- Intuitive UI

## MigMatic® user interface – clean, crisp and easy to use

The MigMatic® system provides a full set of features and settings at your fingertips – ease of use without compromise.



### 1. Four different trigger options:

- 2T
- 4T
- Miller 4TS
- Spot

### 2. Weld processes:

- A. Manual MIG/MAG
- B. Synergic
- C. Synergic Pulse
- D. Synergic Double Pulse

### 3. Adjustment of parameters:

- A. Pre/post gas
- B. Run-in speed
- C. Crater fill
- D. Burnback
- E. Inductance

### 4. Store, modify and recall programs:

- A. A total of 8 programs available
- B. The first 4 recalled using the torch trigger

### 5. System settings and factory reset

## MigMatic® S400iP / MP S400iP components



**MigMatic® Feed 2.0** is equipped with a robust 4 wheel drive mechanism which will last in toughest conditions. The feeder can be suspended from a crane with interconnection cable up to 30 meters. The new design makes in more compact and intuitive for the operator.



**MigMatic® S400iP** benefits from Wind Tunnel Technology™ directing the airflow where it is needed whilst sensitive components are protected from ingress of dust and moisture.



**MigMatic® MP S400iP** is the new multiprocess model in the MigMatic product family which enables lift tig and MMA capabilities.



**MigMatic® Cool** powered by the S400iP is equipped with a low flow alarm and a push button to prime the pump. The tank can hold up to 5 litres of coolant and the system generates 1 kW or 3412 BTU/h.



**MigMatic® Cart** can easily be adjusted to carry both the air and water cooled system. The wheels are large and durable making the system easy to move between work sites.



## Specifications (Subject to change without notice.)



### MigMatic® S400iP

Input Power	Voltage Range in CV	Amp Range DC	Rated Output @ 40°C	IP Rating	Max. Open Circuit Voltage	Dimensions H/W/D	Weight
400 VAC, 3 ph (50/60 Hz)	13 - 42 V	15 - 400 A	400 A / 34 V @ 80% duty cycle	IP23S	70 VDC	530 / 305 / 730 mm	53 kg

### MigMatic® MP S400iP

Mode	Voltage Range in CV	Amp Range DC	Rated Output @ 40°C	IP Rating	Max. Open Circuit Voltage	Dimensions H/W/D	Weight
MIG	13 - 42 V	15 - 400 A	400 A / 34 V @ 100% duty cycle	IP23S	70 VDC	530 / 305 / 730 mm	53 kg
MMA / Stick	–	15 - 400 A	400 A / 36 V @ 100% duty cycle		70 VDC		
TIG Lift-Arc	–	15 - 400 A	400 A / 26 V @ 100% duty cycle		70 VDC		

### MigMatic® Feed 2.0

Input Power	Welding Power Source	Wire Feed Speed	Wire Diameter Range	Welding Circuit Rating	Dimensions H/W/D	Weight
42 VAC, 1 ph (50/60 Hz)	S400i, MP S400iP S400iP, S500i	1.5 - 20 m/min	0.6 - 1.8 mm	39 V, 500 A, 60% duty cycle	465 / 275 / 710 mm	18 kg

### MigMatic® Cool

Coolant Tank Capacity	Maximum Cooling Capacity	Input Power	Cooler on Standby	Cooler Enabled	Dimensions H/W/D	Weight
5 l	1 kW (3412 BTU/h)	400 VAC 50/60 Hz	Volts in: 400 VAC I in: 54 mA Input power (W): 6 Input power (VA): 22	Volts in: 400 VAC I in: 683 mA Input power (W): 237 Input power (VA): 273	292 / 305 / 720 mm	23 kg

## Drive Rolls (∅ 37 mm)

### Drive Rolls for Steel

Groove	Type	Stock No.	Quantity
0.6 - 0.8 mm	Pressure roll	<b>7700000011</b>	x2
	Feed roll	<b>7700000016</b>	x2
0.8 - 1.0 mm	Pressure roll	<b>7700000012</b>	x2
	Feed roll	<b>7700000017</b>	x2
0.9 - 1.1 mm	Pressure roll	<b>7700000013</b>	x2
	Feed roll	<b>7700000018</b>	x2
1.0 - 1.2 mm	Pressure roll	<b>7700000014</b>	x2
	Feed roll	<b>7700000019</b>	x2
1.2 - 1.6 mm	Pressure roll	<b>7700000015</b>	x2
	Feed roll	<b>7700000020</b>	x2

### Drive Rolls for Aluminium

Groove	Type	Stock No.	Quantity
0.8 - 1.0 mm	Drive Rolls	<b>7700000021</b>	x4
1.0 - 1.2 mm	Drive Rolls	<b>7700000022</b>	x4
1.2 - 1.6 mm	Drive Rolls	<b>7700000023</b>	x4

### Drive Rolls for Flux Core

Groove	Type	Stock No.	Quantity
1.2 - 1.6 mm	Drive Rolls	<b>7700000024</b>	x4

## MIG guns – Miller® EuroGun line

Stock No.	EuroGun	Water	Air	Euro connector	Water quick connect	Remote WFS and Volts control on gun	3 meter	4.5 meter	Rating CO <sub>2</sub> gas (A)	Rating Mix gas (A)	Duty cycle (%)
<b>058023005</b>	A-300	-	●	●	-	-	●	-	300	250	100
<b>058023006</b>	A-300	-	●	●	-	-	-	●	300	250	100
<b>058023007</b>	A-300R	-	●	●	-	●	●	-	300	250	100
<b>058023008</b>	A-300R	-	●	●	-	●	-	●	300	250	100
<b>058023001</b>	W-500	●	-	●	●	-	●	-	500	400	100
<b>058023002</b>	W-500	●	-	●	●	-	-	●	500	400	100
<b>058023003</b>	W-500R	●	-	●	●	●	●	-	500	400	100
<b>058023004</b>	W-500R	●	-	●	●	●	-	●	500	400	100

**A** – air cooled   **W** – water cooled   **R** – remote current control on gun

# Ordering Information

System Component	Stock No.	Description	Qty.	Price
MigMatic® S400iP	059015055	400 VAC, 3 ph (50/60 Hz) equipped with mains cable, 3 m		
MigMatic® Feed 2.0	3800000003	Fitted with Euro connector, 1.0 - 1.2 mm "V" groove drive rolls and spool cover		
MigMatic® Multiprocess	3400000003	400 VAC, 3 ph (50/60 Hz) equipped with mains cable, 3 m		
MigMatic® Cool	058042005	1 kW of cooling, 5 l tank capacity		
MigMatic® Cart	058066141	Complete for air- or water-cooled system, incl. swivel for wire feeder		
<b>Interconnection Cables</b>				
Interconnection cable 2.5 m, MigMatic® air	058019368			
Interconnection cable 5 m, MigMatic® air	058019369			
Interconnection cable 10 m, MigMatic® air	058019370			
Interconnection cable 15 m, MigMatic® air	058019371			
Interconnection cable 20 m, MigMatic® air	058019372			
Interconnection cable 30 m, MigMatic® air	058019373			
Interconnection cable 2.5 m, MigMatic® water	058019374			
Interconnection cable 5 m, MigMatic® water	058019375			
Interconnection cable 10 m, MigMatic® water	058019376			
Interconnection cable 15 m, MigMatic® water	058019377			
Interconnection cable 20 m, MigMatic® water	058019378			
Interconnection cable 30 m, MigMatic® water	058019379			
<b>Accessories</b>				
Wheel kit for MigMatic® Feed	028066304			
Return cable kit, 400 A, 70 mm², 5 m	057014340			
Suspension hook	058435	To attach to the wire feeder when suspended from a crane/boom		
Push/Pull configuration kit	057084226	For installation in the feeder to synchronize the drive motors		
14-pin receptacle kit for automation	056076174	For installation in the feeder to facilitate connection with external automation components		
Miller® EuroGun		See section MIG Guns – Miller® EuroGun		
Coolant 3.8 l	043810	2 canisters required to fill the tank		

Date:

Total Quoted Price:

Miller recommends *Elega* consumables

Distributed by:

